

6" Dome

4" Dome



3000 SERIES STROBE

4000 SERIES STROBE

#3(x)(x)(x)(x)(x)

#4227(x)(x)(x)

W F H M C
A L E O L
T A I U L
S H T N O
T

H M C
E O L
I U L
G N O
T

WATTS

3000: Ø=Remote, 1Ø=10 watt, 2Ø=20 watt (4000 is 20 watt)

HEIGHT

L=Low, 4" dome
H=High, 6" dome

COLOR

- A** Amber Lens
- B** Blue Lens
- C** Clear Lens (white)
- G** Green Lens
- R** Red Lens
- J** Red/Blue Split (J in low dome only)

MOUNT

C=Flat/Pipe
M=Magnetic

FLASH

3000: Ø=Remote, 7=Double & Quad (4000 has Double & Quad)




(Strobe Tube 1 Yr.)

(w/ Dust Cover)

Tech Specs	3000 Strobe	4000 Strobe
Input Voltage:	10 - 30 Vdc	
Current Draw:	10 watt: 1 amp @ 12 Vdc, 0.5 amp @ 24 Vdc 20 watt: 2 amps @ 12 Vdc, 1 amp @ 24 Vdc	20 watt: 2 amps @ 12.8 Vdc, 1 amp @ 24 Vdc
Output:	10 or 20 watt	20 watt
Technology:	Xenon Helix Strobe Tube	
Flash Patterns:	2 Flash Patterns - Double or Quad (user selectable)	
Mounting:	Permanent or Magnetic Mount (polycarbonate lens & base)	Permanent or Magnetic Mount (polycarbonate lens & aluminum base)
Dimensions:	4" Dome: 4.6" (12 cm) Height or 6" Dome: 6.5" (17 cm) Height x 6.3" (16 cm) Diameter	

#E36ØBG6
6" BRANCH GUARD



#E36ØDC6
6" DUST COVER

Beacon ACCESSORIES

3000, 4000 & 4500*

- 4" Metal Branch Guard #E36ØBG4
- 6" Metal Branch Guard #E36ØBG6
- Clear Dust Cover #E36ØDC6

*Not For Use with the 5000 Series Economy Strobe Beacon.

Tech Specs	5000 Economy
Input Voltage:	10 - 30 Vdc
Current Draw:	1.5 amp @ 12 Vdc 0.75 amp @ 24 Vdc
Output:	15 watts
Technology:	Xenon "U" Strobe Tube
Flash Patterns:	2 User Selectable Flash Patterns: Double & Quad
Mounting:	Permanent Mount only
Dimensions:	5.5" (14 cm) Height x 7" (18 cm) Diameter

5000 ECONOMY STROBE

Amber Dome #5157LFC
Clear Dome #5157LFA



5" Dome

