

TrafficMaster™

Gen2 LED Directional/Warning Bar



Tech Specs	TrafficMaster™
Flash Patterns:	8 Warning Patterns
Light Sync:	No
Technology:	168 Gen2 LEDs
Mounting:	Surface Mount w/ included Brackets
Input Voltage:	10 - 30 Vdc
Current Draw:	2.2 amps max
Dimensions:	Length x Height x Depth Solid Bar: 42" (1 m) L x 2.75" (70 mm) H x 1.75" (44 mm) D Split Arrow: 21" (53 cm) L (each end) x 2.75" (70 mm) H x 1.75" (44 mm) D
Operating Temp.:	-30° to +65° C / -86° to +149° F

Replacement Parts:

Control Box	#ET2CBTML
Flush Mount Brackets	#ETTMBRKT (pair)
L-Brackets	#PBKTLEDTM (pair)
25' Extension Cable	#ETTMLEXT25
Warning Module	#PLEDTMWA (no arrow)
Arrow End Module	#PLMATMLEDA
Directional Module	#PLMCTMLEDA (no arrow)

TrafficMaster™
#ETTMLED-P



- **Universal design fits interior rear windows** in all types vehicles or can be mounted on the exterior
- **8 sealed weatherproof Gen2 modules**
- **Reliable self-contained solid state design**
- **Includes Control Box & Mounting Brackets**
- **Control Box features illuminated display** to show flash pattern selected & 5-position rotary switch to control all primary functions
- **Hard wire installation with 25' cable**
- **Compatible the DAS, see pg. 25**

Traffic Arrow™

Gen2 LED Directional/Warning Bar



Standard Brackets

Heavy Duty Brackets

Switch Panel



Tech Specs	Traffic Arrow™
Flash Patterns:	3 Total 1 Warning, 2 Directional
Light Sync:	No
Technology:	168 Gen2 LEDs
Mounting:	Surface Mount w/ included Brackets
Input Voltage:	10 - 16 Vdc
Current Draw:	less than 3 amps
Dimensions:	Length x Height x Depth 42" (1 m) L x 2.6" (66 mm) H x 3.3" (84 mm) D
Operating Temp.:	-30° to +65° C / -86° to +149° F

- **Self-contained with 3 Flash Patterns**
- **Glare reducing Sun Shield**
- **Heavy duty design**
- **Economically priced**
- **8 sealed & weatherproof modules** that require little routine maintenance
- **Switch Panel & 2 Brackets included: Standard & Heavy Duty** (most applications will use the Standard brackets) - Heavy Duty Brackets are for high stress applications
- **Compatible the DAS, see pg. 25**

Directional/Warning Bars - TrafficMaster™ & Traffic Arrow™

1.800.338.7337 / www.soundoffsignal.com

Soundoff
Signal