

Directional Arrow Switch



#ETSWDASØ1

- Features 7 programmable Warning Modes & a fully illuminated display shows pattern activated & input selected
- Allows control for multiple directional arrow products with 6-low current (0.25 amps) + 10-30 Vdc outputs
- Made with a durable ABS plastic housing with an adjustable steel bracket
- Built-in Smart Sensor detects inputs from another switching source so it may be used with other manufacturers Directional Arrow products
- Includes Harness with 12" (31 cm) wire length
- For use with LED lighting products ONLY
- Compatible with APEX™, Pinnacle™ (EPL9000), ETL5000™ full sized LED lightbars. May also be used with Pinnacle™ (EPL8000) interior bars, UltraLITE™, TrafficMaster™ & Traffic Arrow™ directional/warning bars

6.5" (17 cm) W x 3.5" (89 mm) H x 1.2" (30 mm) D



900 Series 9 Function Switch



#ETSP9F

- Nine functions with a 3-position slide switch & 6 mini rocker switches
- Slide switch features 20 amps/output with LED indicator ON lights
- Switch has 4 - 20 amp fused switch outputs
- Made with a tough vinyl coated steel housing
- Interchangeable switch labels for easy switch identification: Rotating, Flashing, Rear Flashing, Front Flashing, Aux. 1, Aux. 2, Light Bar, Take Down, Left Alley, Right Alley, Deck Lts., Dash Lts., Grille Lts., & Gun Lock
- Includes Switch box with Universal Bracket, mounting hardware, switch labels & 18" pigtail w/ insulated quick connects for termination

6.2" (16 cm) W x 2.2" (56 mm) H x 5.2" (13 cm) D



600 Series 6 Function Switch



#ETSP6F

- Six mini rocker switches with red LED indicator ON lights
- Features a single 40 amp relay/circuit breaker with 5 - 20 amp fused switch outputs
- Durable ABS plastic housing
- Interchangeable legend labels for easy switch identification. Includes Rotating, Flashing, Aux. 1, Take Down, Left Alley, Right Alley, Strobe, Compartment. Lts., Work Lts., Grille & Deck Lts., Rear Lts. & Front Lt. Cut-Off
- Includes Switch box w/ Universal Bracket, mounting hardware, switch labels & 18" pigtail w/ insulated quick connects for termination

6.2" (16 cm) W x 2.2" (56 mm) H x 5.2" (13 cm) D

