

4500 Series™ LED Beacon



Features

- Magnetic or Permanent Mount options
- May be pipe mounted
- High or Low Dome Heights at 4" & 6"
- Durable lens with UV inhibitor prevents sun fade
- Optional Branch Guard & Dust Cover (for CA Title 13 compliancy)

4500 Series LED

- 1300 Lumen LED output
- Rated to last 20,000+ hours
- Heavy duty cast aluminum base
- Great LED upgrade option with same footprint as our 3000 & 4000 Strobe Beacons



Tech Specs	4500 LED
Input Voltage:	10 - 30 Vdc
Current Draw:	1 amp @ 12 Vdc 0.5 amps @ 24 Vdc
Output:	Amber, Blue, Green, White: 9 watts Red: 6 watts
Technology:	12 Gen3 LEDs
Flash Patterns:	8 Flash Patterns
Mounting:	Permanent or Magnetic Mount
Dimensions:	4" Dome: 4.6" (12 cm) Height 6" Dome: 6.5" (17 cm) Height x 6.3" (16 cm) Diameter



Beacon ACCESSORIES

- 4" Metal Branch Guard #E36ØBG4
- 6" Metal Branch Guard #E36ØBG6
- Clear Dust Cover #E36ØDC6



#E36ØBG6
6" BRANCH GUARD

4500 SERIES LED

#ELB(xx)B(x)(xx)(xx)

C L A S S **M O U N T** **H E I G H T** **C O L O R**

CLASS

- 45=Class 1
- 42=Class 2

MOUNT

- C=Flat/Pipe
- M=Magnetic

HEIGHT

- Magnetic Mount:
- L+=Low, 4" dome
- H+=High, 6" dome
- Flat/Pipe:
- LØ=Low, 4" dome
- HØ=High, 6" dome

COLOR

LED COLOR / DOME COLOR

- A** AA=Amber/Amber
- A** AC =Amber/Clear
- W** WA=White/Amber
- B** BB=Blue/Blue
- G** GG=Green/Green
- R** RR=Red/Red
- W** WC=White/Clear
- J** Red/Blue Split (J in low dome only)

SoundOFF
Signal

4500 LED Beacon

1.800.338.7337 / www.soundoffsignal.com / 2011 New Product Release

Rev. 0811