



3900 Central Parkway
Hudsonville, MI 49426
toll free 800.338.7337
office 616.896.7100

techsupport@soundoffsignal.com
www.soundoffsignal.com

WARNING: Warning devices are strictly regulated and governed by Federal, State and Municipal ordinances. These devices shall be used ONLY on approved vehicles. It is the sole responsibility of the user of these devices to ensure compliance.

⚠ WARNING

This product contains high intensity LED devices. To prevent eye damage, DO NOT stare into light beam at close range.

Refer to Predator Surface Mount instructions for complete details of lamp installation and operation.

MOUNTING INSTRUCTIONS

Note: The Motor Cycle Mount is designed to attach to either 7/8"-1" dia. (PRDSMMSBM) or 1-1/4" dia. (PRDSMMLBM) tubing. DO NOT attempt to install the unit for other than its intended application.

1. Attach clamp unit to vertical portion of crash bar using #8 screws and nuts provided.
2. Discard gasket that is shipped with the Predator Surface Mount Warning Light and install gasket supplied with clamp between shell and light. Gasket provided with clamp MUST be used between light and shell. Screw light to shell. **NOTE: Do Not over tighten screws!**
3. Attach light / shell assembly to clamp by locating unit over ball joint and securing with rear socket half using hex head cap screws.
4. Adjustment of light is accomplished by loosening cap screws and swiveling light to new position. When correct position is achieved retighten screws
5. Make electrical connections and complete installation by ensuring cable has no excessive play.

PREDATOR™

MOTORCYCLE CRASH BAR MOUNTING SYSTEM

ASSEMBLY INSTRUCTIONS

PRDSMMSBM (FITS 7/8"-1" DIA. BAR)

PRDSMMLBM (FITS 1-1/4" DIA. BAR)

