

NEW!



LED3

MINI LIGHT PRODUCTS

by SoundOff Signal



LED3 Mini Spotlight
#EL3SSCW

- The new LED3 Mini Spotlight is a high powered, versatile surface mount light designed for maximum impact with a 45° Flood lens with bright, high bin LEDs for superior light output, efficiency & consistent color.
- Compact size allows you to use it anywhere you have restricted space that needs bright, white output.
- Many versatile mounting options with optional brackets & bezels for a variety of applications.
- Spotlight is made with only the highest quality, high bin LEDs for consistent & pure white LED color.
- Light has a black powder coated aluminum housing with a strong, crystal clear Lexan polycarbonate lens.
- Weatherproof design has superior performance regardless of weather conditions.
- Includes Rubber Mounting Gasket & Mounting Hardware with 18" of 3-Wire Shielded Cable.



Universal Grille Bracket
#EL3SNBRK1GRU



45° Bracket
Vertical #EL3SNBRK145
Horizontal #EL3SNHBRK145



90° Bracket
#EL3SNBRK190



Side-by-Side 90° Bracket
#EL3SNBRK290H



Stacked 90° Bracket
#EL3SNBRK290V (horiz. mount)



Stacked 90° Bracket
#EL3SNBRK290V (vertical mount)



Universal Lic. Plate Bracket:
Horizontal (shown) #EL3SNBRK2LPH
Vertical #EL3SNBRK2LPV

Ford Crown Vic, Chevy Impala
& Dodge Charger (2006) Bracket:
Horiz. Lic. Plate Bracket #EL3SNBRK2LPHE
Vertical Lic. Plate Bracket #EL3SNBRK2LPVE



Single Bezel
#PEL3BZSG(x)



Dual Stacked Bezel
#PEL3BDS(x)



Dual Side-by-Side Bezel
#PEL3BZSS(x)

Bezels available in:
Black=B, Chrome=C, White=W



TECHNICAL SPECIFICATIONS	
Flash Patterns:	None - Steady Burn only
Input Voltage Range:	10 - 16 Vdc
Current Consumption:	less than 0.4 amps
# of LEDs:	3 Gen3 LEDs
Light Sync Technology:	No
Operating Temperature:	-40° to +65° C
Dimensions:	<u>w</u> idth x <u>h</u> eight x <u>d</u> epth
	2.5" w x 1.375" h x 1.25" d 64 mm x 35 mm x 32 mm

SoundOff Signal
LED3 Mini Spotlight
 1.800.338.7337 / www.soundoffsignal.com / 2010 New Product Release
 Rev. 0410