



Deck/Grille Mounts



Single Mount

Solid Color
Split Color

EP2SGS1(x)

EP2SGS2(x)



Dual Side-by-Side Mount

Solid or Split Colors

EP2DGS1(x)

Replace (x) in the Order Number for Standard Color Selection

Solid Colors: A=● B=● G=● R=● W=○

Split Colors: D=●○ E=●○ F=●○ H=●○ J=●○ K=●○ L=●○ M=●○ N=●○ P=●○

Features

- Brackets allow 120 degrees of light head adjustment to angle the light
- Flash pattern recall remembers last flash pattern used
- Convenient side wire exit for easier installation
- Includes 18" of 3-wire cable



Technical Specifications

INPUT VOLTAGE	10-30 Vdc
CURRENT DRAW	Single: 1.1 Amps maximum or Dual Side-by-Side: 2 Amps maximum (flash pattern dependent)
LIGHT SYNC	4
FLASH PATTERNS	33 flash patterns
LED COUNT	Single: 8 LEDs or Dual Side-by-side: 16 LEDs
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	Single Length: 4.3" (11 cm) Height: 2.4" (7 cm) Depth: 1.75" (4.4 cm) Dual Side-by-Side Length: 8.5" (22 cm) Height: 2.4" (7 cm) Depth: 1.75" (4.4 cm)
MOUNTING	Surface mount on 2.77" (7.0 cm) centers
CERTIFICATIONS	SAE J595 Class 1 certified and CA Title 13, Article 22 compliant
WARRANTY	Five-year

1.800.338.7337