



## Deck/Grille Mounts



### Single Mount

Solid Color  
Split Color

EP2SGS1(x)

EP2SGS2(x)



### Dual Side-by-Side Mount

Solid or Split Colors

EP2DGS1(x)

Replace (x) in the Order Number for Standard Color Selection

Solid Colors: A=● B=● G=● R=● W=○

Split Colors: D=●○ E=●○ F=●○ H=●○ J=●○ K=●○ L=●○ M=●○ N=●○ P=●○

### Features

- Brackets allow 120 degrees of light head adjustment to angle the light
- Flash pattern recall remembers last flash pattern used
- Convenient side wire exit for easier installation
- Includes 18" of 3-wire cable



### Technical Specifications

<b>INPUT VOLTAGE</b>	10-30 Vdc
<b>CURRENT DRAW</b>	Single: 1.1 Amps maximum or Dual Side-by-Side: 2 Amps maximum (flash pattern dependent)
<b>LIGHT SYNC</b>	4
<b>FLASH PATTERNS</b>	33 flash patterns
<b>LED COUNT</b>	Single: 8 LEDs or Dual Side-by-side: 16 LEDs
<b>OPERATING TEMPERATURE</b>	-40° C to +65° C / -40° F to +149° F
<b>DIMENSIONS</b>	<b>Single</b> Length: 4.3" (11 cm)    Height: 2.4" (7 cm)    Depth: 1.75" (4.4 cm) <b>Dual Side-by-Side</b> Length: 8.5" (22 cm)    Height: 2.4" (7 cm)    Depth: 1.75" (4.4 cm)
<b>MOUNTING</b>	Surface mount on 2.77" (7.0 cm) centers
<b>CERTIFICATIONS</b>	SAE J595 Class 1 certified and CA Title 13, Article 22 compliant
<b>WARRANTY</b>	Five-year

1.800.338.7337